



	RI-100 PIE RI-100 FREE-STANDING
Potencia <i>Output</i>	7 kW. - 16 kW.
Potencia nominal: <i>Nominal Output</i>	10,78 kW.
Rendimiento <i>Efficiency</i>	87,3 %
Emisiones CO al 13% O ₂ (mg/m ³ al 13% O ₂) <i>Emission CO 13% O₂ (mg/m³ at 13% O₂)</i>	0,08 % (1118,45 mg/m ³)
Emisión de partículas al 13% O ₂ <i>Particle emission at 13% O₂</i>	19,28 mg/m ³
CnHm - OGC (mg/m ³)	36,64 mg/m ³
Nox mg/m ³	74,39 mg/m ³
Sistema de deflectores ajustables <i>Adjustable Baffle system</i>	✓
Entradas de aire primario, secundario y terciario <i>Primary, secondary, and tertiary air supply</i>	✓
Sistema cristal limpio: <i>Air- Wash system</i>	✓
Entrada de aire exterior <i>External air Supply</i>	✓
Modelo estanco <i>Airtight</i>	-
Cajón cenicero <i>Ash pan</i>	✓
Revestimiento interior <i>Interior lining</i>	Vermiculita / Thermic
Peso <i>Weight</i>	210 / 222 Kg.
Certificaciones <i>Certifications</i>	EN 16510 / EN 13240 / CE ECODESIGN / Stufe 2
Clasificación energética <i>Energy label</i>	A+